

Albaplex

Technical Specification

Description: F/C FBB white back (GC1)
Mill: Mayr Melnhof Eerbeek

Board Type: Folding Box
Backing: White
Coating: Full

Coating Weight: 26 gsm
Rev Coating Weight: 5 gsm

PRODUCT SPECIFICATION

Caliper	Gsm	Std	Mill Stiffness Taber 15° mNm	
			MD	CD
320	215	Y	7.70	4.00
370	230	Y	9.30	4.70
410	250	Y	12.00	6.10
460	275	Y	15.90	8.10
510	300	Y	20.60	10.50
570	325	Y	26.10	13.40
620	350	Y	32.50	16.70
670	375	Y	39.90	20.60
730	400	Y	48.40	25.00
790	425	N	57.90	29.90
850	450	N	68.40	35.30
+/- 5%	+/- 2%		- 15%	- 15%

TEST DATA

Property	Test	Value	UOM	Tolerance
Smoothness	ISO 8791-4	2.0	ums	2.5
Brightness - top	ISO 11475	84	%	+/- 1
Brightness - reverse	ISO 11475	84	%	+/- 1
Gloss	ISO 2813	14	%	+/- 2% 60 deg
Moisture content	EN 20287	7.5 - 9	%	+/- 1%

TEST & TECH. NOTES

MAKING NOTES

Minimum sheet size 420 x 450 mm
Maximum sheet size 1450 x 1600 mm LG only - base runners run lengthwise
When either size >1400 mm, min pallet weight = 1t

QUANTITY TOLERANCES

ORDERING INFORMATION

< 1 t +/- 20%
1 - 2.5 t +/- 15%
2.5 - 5 t +/- 7.5%
> 5 t +/- 5%