

Albatros H/S

Technical Specification

Description: F/C H/S FBB Cream Back (GC2)
Mill: Buchmann Carton, Cheshire t

Board Type: Folding Box
Backing: Cream
Coating: Full
Hardsized: Yes

Coating Weight: 22-25

PRODUCT SPECIFICATION

Caliper	Gsm	Std	Mill Stiffness Taber 15° mNm	
			MD	CD
400	250	Y	12.90	4.90
460	280	Y	17.20	6.80
495	300	Y	19.90	8.50
525	320	Y	24.30	10.20
570	350	Y	30.10	12.70
640	400	Y	43.20	17.00
+/- 5%	+/- 2%		- 15%	- 15%

TEST DATA

Property	Test	Value	UOM	Tolerance
Brightness (Top)	ISO 2470	84	%	+/- 1.5
Cobb (180s) Reverse	DIN EN 20535	Max 50	gsm	

TEST & TECH. NOTES

MAKING NOTES

Min width 400mm. Max reel width 2400, Max reel size 1300 x 1600mm.
Core Sizes 150, 200, 300. Dely to Ireland & Scotland add £20/tonne.
All 1-1.9t orders must be delivered via Leicester. Min quantity 1 tonne.
FSC material available upon application for an additional £20/tonne

QUANTITY TOLERANCES

ORDERING INFORMATION

1000 - 1999 Kgs +/- 20%
2000 - 4999 Kgs +/- 10%
5000 Kgs plus +/- 5%