

# Korsnäs White

## Technical Specification

**Description:** F/C SUS white back (GN1)  
**Mill:** Korsnas Frovi Ltd - London N14

**Board Type:** Folding Box  
**Backing:** White  
**Coating:** Full  
**Hardsized:** Yes

**Coating Weight:** 22 gsm  
**Rev Coating Weight:** 6 gsm

### PRODUCT SPECIFICATION

Caliper	Gsm	Std	Mill Stiffness Taber 15° mNm		Tear Resistance mN	
			MD	CD	L*T	mN
330	240	Y	12.10	5.30	*****	0
370	265	Y	14.70	7.20	*****	0
430	290	Y	22.20	11.10	*****	0
480	320	Y	30.00	14.70	*****	0
525	345	Y	36.00	18.80	*****	0
580	380	Y	46.60	25.10	*****	0
645	410	Y	59.40	31.90	*****	0
+/- 6	+/- 5		- 20%	- 20%		

### TEST DATA

Property	Test	Value	UOM	Tolerance
Smoothness	PPS - 10 TS	1.0	ums	
Brightness - Top	ISO 2470	90	%	-2%
Brightness - Bottom	ISO 2470	85	%	-2%
Cobb - both		35	gsm	
Moisture content		7.3-8.3	%	
Scott Bond		150	J/m2	

### TEST & TECH. NOTES

\*For 320-410 gsm  
Tolerance for 240-290 gsm is +/- 6%

### MAKING NOTES

Minimum sheet size 300 x 400 mm  
Maximum sheet size 1320 x 1650 mm or 1650 x 1320 mm  
Reels: Diameter 1750 mm - Min reel width 700 mm, max reel width 2400 mm  
Reels: Diameter 1500 mm - Min reel width 600 mm, max reel width 2400 mm

### QUANTITY TOLERANCES

All quantities:-1%/+5%

### ORDERING INFORMATION