

U/L G/board MG (L)

Technical Specification

Description: Unlined Greyboard MG (GK)
Mill: Leinfelder, GERMANY.

Board Type: Unlined
Backing: Grey
Coating: Uncoated

Recycled Content: 100%

PRODUCT SPECIFICATION

| Caliper | Gsm | Std | Mill Stiffness Taber 15° mNm | |
|---------|--------|-----|------------------------------------|---------|
| | | | MD | CD |
| 420 | 300 | N | 0.00 | 0.00 |
| 450 | 320 | Y | 0.00 | 0.00 |
| 490 | 350 | Y | 0.00 | 0.00 |
| 550 | 400 | Y | 0.00 | 0.00 |
| 620 | 450 | Y | 0.00 | 0.00 |
| 700 | 500 | Y | 0.00 | 0.00 |
| 780 | 550 | Y | 0.00 | 0.00 |
| 850 | 600 | Y | 0.00 | 0.00 |
| 920 | 650 | Y | 0.00 | 0.00 |
| 1000 | 700 | Y | 0.00 | 0.00 |
| 1060 | 750 | Y | 0.00 | 0.00 |
| 1120 | 800 | Y | 0.00 | 0.00 |
| 1200 | 850 | Y | 0.00 | 0.00 |
| 1280 | 900 | Y | 0.00 | 0.00 |
| 1360 | 950 | Y | 0.00 | 0.00 |
| +/- 5% | +/- 5% | | +/- 15% | +/- 15% |

TEST & TECH. NOTES

MAKING NOTES

Minimum sheet size 420 x 520 mm LG. Guillotining available for smaller sizes.
Maximum sheet size 2750 x 1790 mm SG
Surcharges may apply for large sheet sizes - min 2t
Bundled: £25/t

QUANTITY TOLERANCES

<=4999 kgs: +/- 20%
5000-9999 kgs: +/- 15%
>=10000 kgs: +/- 10%

ORDERING INFORMATION