

Multiboard Offset

Technical Specification

Description: F/C WLC grey back (GD2)
Mill: Fiskeby Board Ltd, Aylesbury, Bucks

Board Type: Chip
Backing: Grey
Coating: Full

Coating Weight: 25 gsm
Recycled Content: 100

PRODUCT SPECIFICATION

| Caliper | Gsm | Std | Mill Stiffness Taber 15° mNm | |
|---------|--------|-----|------------------------------------|-------|
| | | | MD | CD |
| 385 | 280 | Y | 13.30 | 4.80 |
| 415 | 300 | Y | 16.20 | 5.80 |
| 455 | 325 | Y | 20.30 | 7.20 |
| 490 | 350 | Y | 24.90 | 8.90 |
| 530 | 375 | Y | 29.90 | 10.90 |
| 570 | 400 | Y | 36.00 | 13.00 |
| 605 | 425 | Y | 43.00 | 15.50 |
| 645 | 450 | Y | 50.70 | 18.40 |
| +/- 5% | +/- 3% | | -15% | -15% |

TEST DATA

| Property | Test | Value | UOM | Tolerance |
|------------|--------------|-------|-----|-----------|
| Brightness | ISO (R457) | 79 | % | Min 78% |
| Whiteness | ISO (D65/10) | 84 | % | |

TEST & TECH. NOTES

4 gsm reverse side sealer coating

MAKING NOTES

Min sheet size: 450 x 550 mm LG
Max sheet size: 2100 x 1600 mm SG

QUANTITY TOLERANCES

<5 tonnes: +/- 15%
5-15 tonnes: +/- 10%
>15 tonnes: +/- 5%

ORDERING INFORMATION