

PankaBrite H/S

Technical Specification

Description: F/C FBB cream back (GC2)
Mill: Pankaboard

Board Type: Folding Box
Backing: Cream
Coating: Full
Hardsized: Yes

PRODUCT SPECIFICATION

Caliper	Gsm	Std	Mill Stiffness	
			MD	CD
430	275	N	20.00	8.50
480	300	N	26.30	11.70
530	325	Y	32.50	14.50
580	350	Y	39.50	17.50
640	375	Y	46.40	20.60
690	400	Y	55.40	24.60
740	425	Y	65.10	28.90
800	450	Y	74.80	33.20
855	475	Y	86.50	38.50
910	500	Y	97.60	43.40
1000	550	Y	123.90	55.10
+/- 5%	+/- 4%		-15%	-15%

TEST DATA

Property	Test	Value	UOM	Tolerance
ISO Brightness C/2	ISO 2470	%	85	+/- 1.5
Surface smoothness	PPS 10/ISO8791-4	ums	1.0	+/- 0.3
Gloss 75	ISO 8254-1	%	40	>40
Scott Bond	Tappi 569	J/m2	110	>110
Cobb 180s		gsm	<50	

PankaBrite H/S

Technical Specification

Description: F/C FBB cream back (GC2)

Mill: Pankaboard

Board Type: Folding Box

Backing: Cream

Coating: Full

Hardsized: Yes