

Pirol

Technical Specification

Description: F/C WLC grey back (GD2)
Mill: Buchmann Carton, Cheshire t

Board Type: Chip
Backing: Grey
Coating: Full

Coating Weight: 20
Recycled Content: 80-100%

PRODUCT SPECIFICATION

Caliper	Gsm	Std	Mill Stiffness Taber 15° mNm	
			MD	CD
240	210	Y	2.90	1.50
260	230	Y	3.60	1.90
290	250	Y	4.60	2.50
365	280	Y	9.70	4.40
390	300	Y	11.70	5.10
416	320	Y	14.10	6.10
455	350	Y	17.50	8.00
495	380	Y	22.30	10.20
520	400	Y	25.70	11.70
590	450	Y	35.50	17.50
660	500	Y	47.60	24.30
730	550	Y	60.70	30.10
+/- 5%	+/- 2%		-15%	-15%

TEST DATA

Property	Test	Value	UOM	Tolerance
Brightness Top	ISO2470	82.5	%	+/-1

TEST & TECH. NOTES

MAKING NOTES

Min width 400mm.
All orders are to be delivered direct.
Delivery to Ireland & Scotland add £20/Tonne.
415 microns is a non-std caliper, Min qty 1Tonne

QUANTITY TOLERANCES

ORDERING INFORMATION

1 - 2499 Kilos - +/- 15%
2500 - 4999 Kilos - +/- 7%
5 Tonnes Plus - +/- 5%