

Silvaboard

Technical Specification

Description: F/C FBB cream back (GC2)
Mill: Mayr Melnhof Eerbeek

Board Type: Folding Box
Backing: Cream
Coating: Full

Coating Weight: 25 gsm

PRODUCT SPECIFICATION

| Caliper | Gsm | Std | Mill Stiffness Taber 15° mNm | |
|---------|-------|-----|------------------------------------|-------|
| | | | MD | CD |
| 360 | 215 | Y | 10.00 | 5.20 |
| 390 | 230 | Y | 12.00 | 6.10 |
| 440 | 250 | Y | 15.70 | 8.00 |
| 490 | 275 | Y | 21.30 | 10.80 |
| 550 | 300 | Y | 27.20 | 13.80 |
| 600 | 325 | Y | 33.80 | 17.20 |
| 660 | 350 | Y | 41.90 | 21.30 |
| 715 | 375 | Y | 50.70 | 25.90 |
| 775 | 400 | Y | 60.50 | 30.90 |
| +/-5% | +/-2% | | -15% | -15% |

TEST DATA

| Property | Test | Value | UOM | Tolerance |
|------------|---------|-------|-----|----------------|
| Smoothness | | | | |
| Brightness | Elrepho | 87 | % | +/-1 |
| Gloss | ISO2813 | 15 | % | /+/- 2 60 degs |

TEST & TECH. NOTES

MAKING NOTES

Min size: 420 x 450 mm

Max size: 1450 x 1600 mm LG - base runners run lengthwise

When either size >1400 mm, min pallet weight = 1t

QUANTITY TOLERANCES

ORDERING INFORMATION

< 1 t +/- 20%
1 - 2.5 t +/- 15%
2.5 - 5 t +/- 7.5%
> 5 t +/- 5%